

# PROTECH LED

be creative



## COB STRIP SPECIFICATION

AT-RGB-COB-SIDE





## AT-RGB-COB-SIDE

### DESCRIPTION

Side emitting cob led strip, dotless, no hot spot.  
24V, Step length: 100mm with 3M adhesive tape  
on the back for easy installed. 180° beam angle.  
Very good color reproduction with CRI>90.



### DIMENSIONS & WATERPROOF



### PRODUCT SPECIFICATION

Dimension	5000 x 10 x 2mm
Chio Type	COB
Chips/m	630 LEDs/m
Step LEDs	63 LEDs
Cutting Length	100mm

Voltage (V)	DC24V
Current (A/m)	0.375 A
Power (W/m)	9W
Beam Angle	180°
Operation Temperature	-20°C~45°C

### PRODUCT PHOTOMETRICS


CCT (K)	Lumen (lm/m)	Efficacy (lm/w)	CRI	Power
RED	40	10	/	4.0
GREEN	125	50	/	2.5
BLUE	15	6	/	2.5
RGB	180	20	/	9.0

\* the given electrical data reflect typical values, each can vary up to 10%.




## AT-RGB-COB-SIDE

### TEMPERATURE CURVE



The above curves indicate the temp. changing in glue & PCB within 30 minutes after powering on, under the ambient temperature of 25°C. The following charts shows the parameters on each meter based on 8M length.

### BRIGHTNESS CONSISTENCY



From above chart, please connect 8M at most by one-end power to keep brightness consistency