

PROTECH LED

be creative



LED STRIP SPECIFICATION

AT-RGB-PIXEL-5V-2





AT-RGB-PIXEL-5V-2

DESCRIPTION

AT-RGB-PIXEL-5V-2 RGB magic LED strip lights let you create millions of colors by just mixing red, green, and blue colors. With the ability to control each individual pixel and each individual channel, the color mix and color effects possibilities are endless. LED Chip is built-in IC SK6812, supporting numerous Color-change effects every single LED. Fully compatible with IC WS2812B. Flexible PCB 5V low voltage input.

DIMENSIONS & WATERPROOF

Dimension	
IP Grade	

PRODUCT SPECIFICATION

Dimension	5000x10x2.2mm	Voltage (V)	DC5V
Chip Type	5050SMD	Current (A/m)	2.12A
Chip Density	60 LEDs/m	Power (W/m)	10.6W (3 colors 100% on)
Step LEDs	1 LED	Beam Angle	120°
Step Length	16.54 mm	Operation Temperature	-20°C~50°C

PRODUCT PHOTOMETRICS - RED, GREEN AND BLUE DIODES (DATA BASE ON IP20)

Color	Lumen (LM/M)	Power (W/M)	Efficacy (LM/W)
RED	59	3.5	16.9
GREEN	178	3.5	50.7
BLUE	45	3.5	12.8
RGB	268	10.6	25.3



AT-RGB-PIXEL-5V-2

- IP20: bare, max. light output and the best color consistency, indoor use.
- IP52: silicone coating, ~5% less output and 3rd best color consistency, indoor use, for damp environments.
- IP65: silicon tube/Heat shrink tube/Extrusion tube/U milky tube + clear cover, ~3% less output and 2nd best color consistency, indoor use or semi-outdoor use, for raining environments.
- IP67: silicone tube + siliconfilling, ~7% less output and 4th best color consistency, outdoor use, max length is 10 meters.
- IP67E: solid silicone extrusion, ~7% less output and 4th best color consistency, outdoor use, max length up to 50 meters.
- IP68: PU (Polyurethane), ~7% less output and 4th best color consistency, under the water, within 2 meters deep.

WIRING DIAGRAM

